

Electronic Timer Control - Electronic All-Purpose Contractor Box, 120 - 480 VAC, 60 Hz, 3PST, Outdoor Metal Enclosure

Item ETCB28253PCR



PRODUCT DESCRIPTION

The ETCB28253PCR Electronic All-Purpose Contractor Box provides an easy-to-install solution for a variety of application needs. The Contractor Box comes with a pre-installed Astronomic timer with 7-day, holiday/exception period scheduling, USB for Schedule transfer and Backup, a 60 A contactor, as well as inputs for overrides and surge protective devices.

FEATURES

- ▶ 7-Day/365 Day Astronomic Scheduling
- ▶ Up to 96 Scheduling set points
- ▶ Up to 50 Holiday/Exception Period set points
- ▶ USB port for backing up or transferring schedules
- ▶ Built-in 60 A 3-Pole contactor for more robust loads
- ▶ Input for optional "Timed" photo control override
- ▶ Input for other types of switches/sensors
- ▶ Terminals for adding Surge Protection
- ▶ 100-hour supercapacitor eliminates the need for battery replacement
- ▶ Requires 120 VAC 60 Hz for powering the control

APPLICATIONS

- ▶ Electric Fans
- ▶ Electric Motor Control
- ▶ Electric Pumps
- ▶ Exhaust Fans
- ▶ Parking Lot Lighting
- ▶ Sign Lighting
- ▶ Sports Fields

TECHNICAL DATA

General	
Model Number	ETCB28253PCR
Description	Electronic All-Purpose Contractor Box, 120 - 480 VAC, 60 Hz, 3PST, Outdoor Metal Enclosure
UPC Code	078275152472
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty	2-Year limited
Control Specifications	
Minimum ON/OFF Times	1 min
Minimum Pulse Time	2 sec
Maximum ON/OFF Times	Indefinite
Maximum ON/OFF Operations	96
ON/OFF Operations	96
Operation Features	Astronomic; Holiday; Override
Backup Type	Supercapacitor
Backup Protection Time	100 Hour
Mechanical Specifications	

Enclosure Type Indoor/outdoor type 3 metal

Dimensions

Product Dimensions (H x W x D) in	11.75 x 10 x 4.75 in
Wire Size Min	#14 AWG
Wire Size Max	#4 AWG (Load Side)
Knockout Dimensions Bottom	(7) 1/2" - 3/4" combination, (2) 3/4" - 1" combination
Knockout Dimensions Back/Side	(4) 1/2" - 3/4" combination, (1) 3/4" - 1" combination
Knockout Dimensions Left	(4) 1/2" - 3/4" combination
Knockout Dimensions Right	(4) 1/2" - 3/4" combination

Load Ratings

Resistive (NO) Range(s)	60 A
Motor (NO) Range(s)	5 HP, 120 VAC;10 HP, 240 VAC, (Single-Phase);25 HP (360 LRA), 240 VAC;30 HP (300 LRA), 480 VAC

Electrical Specifications

Switch Type	3xSPST
-------------	--------

Packaging

Shipping Weight (lbs)	14
Unit Carton Dimensions (H x W x L) in	6.375 x 13.25 x 13.5 in

Environmental Specifications

Temperature (operation)	-40 °F to 104 °F / (-40 °C to 40 °C)
-------------------------	--------------------------------------

Standards and Certifications

UL Certification	cULus
California Proposition 65	Nickel; Lead
PDF Standards and Certifications	cULus